

EXTREME WEATHER EXTENSION CORD



- Rugged jacket
- Flexible
- Receptacle lights up when the cord is powered
- Blue with a red stripe
- -94°F Temperature range: no cracking or breaking
- Maximum flexibility
- Resists Abrasion, Grease, Oil and Water
- Unbreakable, molded-on connectors
- Every cord is tested
- Indoor/outdoor use
- Contractor approved
- Meets all UL & OSHA requirements
- Made in the USA

CONSTRUCTION:

Highly flexible annealed 30 gauge bare copper conductors, insulated with a TPE (thermoplastic elastomer) SJEOW jacket. Operating temperatures range from -70°C to +105°C (-94°F to +221°F). The 12 gauge, 3 conductors are rated at 125V, 15A (1875W). Stocked in blue with a red striped jacket. Stocked lengths are 25, 50 and 100 ft. Standard sleeved packaging, boxed or shrink wrap packaging available upon request.

APPLICATION:

Designed for indoor and outdoor heavy industrial use. These cords are flexible, durable and manufactured in the USA, to meet or exceed all UL and OSHA requirements.

GAUGE	STRANDING	RATING	LENGTH	BOX QTY	WEIGHT/UNIT
12/3	#30	15A	25 ft.	12	3.50 lbs.
12/3	#30	15A	50 ft.	4	7.75 lbs.
12/3	#30	15A	100 ft.	2	15.50 lbs.

DIRECT WELDING DIVISION


22 Industrial Way, P.O. Box 57 Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Las Vegas, Portland, Houston

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

Made in USA
www.directwireusa.com

TRIPLE TAP EXTENSION CORD



- Rugged jacket
- Flexible
- Receptacle lights up when the cord is powered
- -35°F Temperature range: no breaking or cracking
- Resists Abrasion, Grease, Oil and Water
- Unbreakable, molded-on connectors
- Every cord is tested
- Indoor/outdoor use
- Contractor approved
- Meets all UL & OSHA requirements
- Made in the USA

CONSTRUCTION:

Highly flexible annealed 30 gauge bare copper conductors, insulated with a vinyl SJTW jacket. Operating temperatures range from -37 °C to +91°C (-35°F to +195°F). The 12 gauge, 3 conductors are rated at 125V, 15A (1875W). Available with a yellow jacket. Stocked lengths are 25, 50 and 100 ft. Triple outlet head for multiple tool convenience. Standard sleeved packaging, boxed or shrink wrap packaging available upon request.

GAUGE	STRANDING	RATING	COLOR	LENGTH	BOX QTY.	WEIGHT/UNIT
12/3	#30	15A	Yellow	25 ft.	12	3.85 lbs.
12/3	#30	15A	Yellow	50 ft.	4	7.75 lbs.
12/3	#30	15A	Yellow.	100 ft.	2	15.50 lbs.

APPLICATION:

Designed for indoor and outdoor heavy industrial use. These cords are flexible, durable and manufactured in the USA, to meet or exceed all UL and OSHA requirements.

DIRECT WELDING DIVISION

22 Industrial Way, P.O. Box 57 Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Las Vegas, Portland, Houston

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

Made in USA
www.directwireusa.com