



- Rugged jacket
- Flexible
- Receptacle lights up when the cord is powered
- Resists abrasion and water
- Unbreakable, molded-on connectors
- Every cord is tested
- Indoor/outdoor use
- Contractor approved
- Meets all UL & OSHA requirements

CONSTRUCTION:

Highly flexible annealed 30 gauge bare copper conductors, insulated with an STW water-resistant jacket. Operating temperatures range from -40°C to +90°C (-40°F to 194°F). The 8 gauge, 3 conductors are rated at 250V, 50A. Stocked lengths are 25 and 50ft. Coiled, boxed and shrink wrap packaging available.

GAUGE	STRANDING	RATING	LENGTH	BOX QTY	WEIGHT/UNIT
8/3	#30	50A	25 ft.	1	8 lbs.
8/3	#30	50A	50 ft.	1	16 lbs.

APPLICATION:

Designed for indoor and outdoor heavy industrial use. These cords are flexible, durable and manufactured to meet or exceed all UL and OSHA requirements.

DIRECT WELDING DIVISION

22 Industrial Way, P.O. Box 57 Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Las Vegas, Portland, Houston

Specifications contained herein reflect current data and are subject to change.
Values are nominal and or approximate.

Made in USA
www.directwireusa.com