

BULK CABLE



- Safety liner for your protection
- Custom insulation designed for maximum field flexibility
- Sequentially marked cable available
- Custom imprinted cable available with quick turnaround
- Colors (Red, Blue, Green, Yellow) available
- Highly flexible soft annealed #30 copper stranding
- Oil, water, sunlight resistant
- UL and MSHA approved

CONSTRUCTION:

Highly flexible stranded No. 30 bare copper conductor insulated with high grade TPE and then jacketed with durable TPE. A high strength fiber braid is added between the insulation and the jacket providing extra strength. Operating temperatures range from -40°C to 90°C dry and 75°C wet. Rated voltage up to 2000V.

APPLICATION:

Gen-Flex single conductor PPE/PPC portable power cable is designed for heavy duty industrial power applications such as temporary or permanent power, including portable generators, air conditioning, grounding, power extension, shore power, mining and oil drill applications. Type PPE is constructed like Type W cable and per article 400 in the NEC and may be used in applications where Type W cables are used.

PART #s	GAUGE	LENGTH	WEIGHT (LB. APPX)	DESCRIPTION
GF08R050014	#8	500'	63#	#8 GF BLK 500' REEL
GF06R050014	#6	500'	92#	#6 GF BLK 500' REEL
GF04R050014	#4	500'	125#	#4 GF BLK 500' REEL
GF02R050014	#2	500'	176#	#2 GF BLK 500' REEL
GF01R050014	#1	500'	217#	#1 GF BLK 500' REEL
GF10R050014	1/0	500'	256#	1/0 GF BLK 500' REEL
GF20R050014	2/0	500'	308#	2/0 GF BLK 500' REEL
GF30R050014	3/0	500'	370#	3/0 GF BLK 500' REEL
GF40R030014	4/0	300'	449#	4/0 GF BLK 300' REEL

Note: Other size reels are available upon request
Note: Bold Lines Indicate Stock

DIRECT WELDING DIVISION

22 Industrial Way, P.O. Box 57 Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Las Vegas, Portland, Houston

Specifications contained herein reflect current data and are subject to change.
Values are nominal and or approximate.

Made in USA
www.directwireusa.com



- Safety liner for your protection
- Custom insulation designed for maximum field flexibility
- Sequentially marked cable available
- Custom imprinted cable available with quick turnaround
- Colors (Red, Blue, Green, Yellow) available
- Highly flexible soft annealed #30 copper stranding
- Oil, water, sunlight resistant
- UL and MSHA approved

CAM-LOK ASSEMBLIES AND BULK CABLE

CONSTRUCTION:

Highly flexible stranded No. 30 bare copper conductor insulated with high grade TPE and then jacketed with durable TPE. A high strength fiber braid is added between the insulation and the jacket providing extra strength. Operating temperatures range from -40°C to 90°C dry and 75°C wet. Rated voltage up to 2000V.

APPLICATION:

Gen-Flex single conductor PPE/PPC portable power cable is designed for heavy duty industrial power applications such as temporary or permanent power, including portable generators, air conditioning, grounding, power extension, shore power, mining and oil drill applications. Type PPE is constructed like Type W cable and per article 400 in the NEC and may be used in applications where Type W cables are used.

PART #s	GAUGE	LENGTH	CARRY STRAP	AMP	WEIGHT	DESCRIPTION
GF020102515	#2	25'	Yes	100	10#	#2 GF BLK 25' W/M&F CAM W/STRAP
GF020105015	#2	50'	Yes	100	19#	#2 GF BLK 50' W/M&F CAM W/STRAP
GF020110011	#2	100'	No	100	39#	#2 GF BLK 100' W/M&F CAM
GF200202515	2/0	25'	Yes	200	17#	2/0 GF BLK 25' W/M&F CAM W/STRAP
GF200205015	2/0	50'	Yes	200	33#	2/0 GF BLK 50' W/M&F CAM W/STRAP
GF200210011	2/0	100'	No	200	66#	2/0 GF BLK 100' W/M&F CAM
GF400202515	4/0	25'	Yes	400	24#	4/0 GF BLK 25' W/M&F CAM W/STRAP
GF400205015	4/0	50'	Yes	400	48#	4/0 GF BLK 50' W/M&F CAM W/STRAP
GF400210011	4/0	100'	No	400	96#	4/0 GF BLK 100' W/M&F CAM

Custom length assemblies and bulk cable available upon request.
Note: 100' length have standard strap, not Direct Power "Easy" Carry Strap.

DIRECT WELDING DIVISION

22 Industrial Way, P.O. Box 57 Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Las Vegas, Portland, Houston

Specifications contained herein reflect current data and are subject to change.
Values are nominal and or approximate.

Made in USA
www.directwireusa.com