

12/3 GFCI CORDS



- Rugged jacket
- Flexible
- Resists Abrasion, Grease, Oil and Water
- Unbreakable, molded-on connectors
- Every cord is tested
- Indoor/outdoor use
- Contractor approved
- Meets all UL & OSHA requirements
- Made in the USA

CONSTRUCTION:

Highly flexible annealed 30 gauge bare copper conductors, insulated with a vinyl SJTW jacket. Operating temperatures range from -37 °C to +91°C (-35°F to +195°F). The 12 gauge, 3 conductors are rated at 125V, 15A (1875W).

APPLICATION:

Designed for construction sites. Ideal for industrial applications, marinas, etc.

PART #	DESCRIPTION	AMPS	VOLTS	WATTS	LENGTH
4021230002510	TRI TAP GFCI	15A	120V	1800W	2 ft.
4021230002520	TRI TAP GFCI 90°	15A	120V	1800W	2 ft.
4021230006900	QUAD BOX GFCI	15A	125V	1875W	6 ft.

DIRECT WELDING DIVISION

22 Industrial Way, P.O. Box 57 Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Las Vegas, Portland, Houston

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

Made in USA
www.directwireusa.com